

SILICONE RUBBER INLAGE
OP ROL
KLEUR = grijs

KOŇAŘÍK[®]
závěsová technika



DESCRIPTION:

Silicone profiles are used in wide range of pipe clamps.

Silicone/slide rubber lining is used on the pipes with operating temperature up to 225°C or where the pipes must be fixed as sliding point. Thanks the silicone/slide rubber lining is resistant to high temperatures and do not prevents the natural dilatation of the pipe

TECHNICAL DATA OF SILICONE LINING:

Material:

silicone

Colour:

grey

Use within temperature range:


from -50°C to +225°C

Supply No.	Name	Thickness	Width	Package
		T (mm)	K (mm)	Mtr.
40202000	Silicone/sliding profile 20×3,5 mm	3,5	20	50
40202500	Silicone/sliding profile 25×4,5 mm	4,5	25	50

CROSS-REFERENCE TABEL :

Konarik Partnr.	WT ARTIKELNUMMER			Inhoud					
	Industrial pack	WT system	WT system	I-pack/Pcs		R-pack/pcs		S-pack/Mtr	
	Fabric pack	Retail pack	Small pack	Pack	Carton	Pack	Carton	Pack	Carton
40202000	IDRSFZM-SBG2006-50MT	x	x	1	10				
40202500	IDRSFZM-SBG2506-50MT	x	x	1	10				

40202000



40202500

