



KRIMPKOUS

3:1 DUNWANDIG

STANDAARD UITVOERING



Deze universeel toepasbare krimpkous voldoet aan de MIL en UL 224 specificaties en is geschikt voor zeer vele protectie-, bundeling- en isolatietoepassingen. Deze krimpkous dekt ongeveer 70 tot 80% van de krimpkous toepassingen. Beschikbaar in een aantal kleuren en verschillende verpakkingsvormen.

	Test methods	Typical data	Result
SHRINK TEMPERATURE	Company standard	90°C	105°C
OPERATING TEMPERATURE RANGE	UL 224	-55°C-125°C	-55°C-125°C
RADIAL SHRINKING CHANGE	ASTM D2671	≥ 50%	55%
LONGITUDINAL CHANGE	ASTM D2671	-5% - 5%	-5% - 5%
TENSILE STRENGTH (MPA)	ASTM D638	≥ 10.4	14.0
ELONGATION AT BREAK	ASTM D638	≥ 200%	400%
TENSILE STRENGTH AFTER AGING (MPA)	ASTM D638	≥ 7.3	9.3
ELONGATION AT BREAK AFTER AGING	ASTM D638	≥ 100%	200%
VOLUME RESISTANCE (Ω.CM)	ASTM D2671	≥ 1.0*10 ¹²	≥3.6*10 ¹⁰
DIELECTRIC STRENGTH	UL 224, AC 2500V, 1 min	No breakdown	No breakdown
HEAT SHOCK	UL 224, 136°C, 168 hrs	No cracking	No cracking
FLAMMABILITY	UL 224, -30°C, 1 hr	No cracking	No cracking
CONCENTRICITY	ASTM D2671	≥70%	75%



features:

SHRINK RATIO:	3:1
MATERIAL:	Polyolefin
FLAMMABILITY:	VW-1

- Excellent acid fastness and corrosion resistance
- UL and RoHS compliant
- Halogen free

CROSS REFERENCE TABEL

Fabric Partnr.	WT ARTIKELNUMMER			Inch maat	KRIMP in MM		I-pack/pcs Pack Carton		Inhoud R-pack/pcs Pack Carton		S-pack/pcs Pack Carton	
	Industrial pack Fabric pack	WT system Retail pack	WT system Small pack		Voor	Na						
612001B	CT31IAEZW000150M0200	x	x	1/16	1.5	0.5	200	2000				
612002B	CT31IAEZW000300M0200	x	x	1/8	3	1	200	2000				
612003B	CT31IAEZW000450M0100	x	x	3/16	4.5	1	100	1000				
612004B	CT31IAEZW000600M0100	x	x	1/4	6	2	100	1000				
612005B	CT31IAEZW000900M0100	x	x	3/8	9	3	100	1000				
612006B	CT31IAEZW001200M0100	x	x	1/2	12	4	100	1000				
612007B	CT31IAEZW001500M0100	x	x	5/8	15	5	100	1000				
612008B	CT31IAEZW001800M0100	x	x	3/4	18	6	100	1000				
612009B	CT31IAEZW002400M0050	x	x	1	24	8	50	500				
612010B	CT31IAEZW003000M0050	x	x	1 1/4	30	10	50	500				
612011B	CT31IAEZW003900M0050	x	x	1 1/2	39	13	50	500				

Gebruik deze gereedschappen :

