



ZODZ.E485779 Positioning Devices

[Page Bottom](#)

Positioning Devices

[See General Information for Positioning Devices](#)

YY CABLE ACCESSORIES CO LTD

E485779

88 SHEN LI RD

JEN-TEH HSIANG, TAINAN HSIEN 717 TAIWAN

Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating
		Min	Max		Min	Max		
ST-1100-LHD	2	12.7 (0.500)	304 (11.97)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-1100-S	2	12.7 (0.500)	304 (11.97)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-1200-LHD	2	12.7 (0.500)	355 (13.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-1200-S	2	12.7 (0.500)	355 (13.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-1250-S	2	12.7 (0.500)	380 (14.96)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-130-S	2	12.7 (0.500)	25 (0.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-150-S	2	12.7 (0.500)	33 (1.30)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-200-LHD	2	12.7 (0.500)	51 (2.01)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-200-S	2	12.7 (0.500)	51 (2.01)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-260-LHD	2	12.7 (0.500)	69 (2.72)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-260-S	2	12.7 (0.500)	69 (2.72)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-280-S	2	12.7 (0.500)	73 (2.87)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-300-LHD	2	12.7 (0.500)	80 (3.15)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-300-S	2	12.7 (0.500)	80 (3.15)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-360-LHD	2	12.7 (0.500)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-360-S	2	12.7	102	445 (100)	-60	300	Yes	AH-1

		(0.500)	(4.02)		(-76)	(572)		
ST-520-LHD	2	12.7 (0.500)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-520-S	2	12.7 (0.500)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-680-LHD	2	12.7 (0.500)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-680-S	2	12.7 (0.500)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST-840-LHD	2	12.7 (0.500)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST-840-S	2	12.7 (0.500)	254 (10.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-1100-LHD	2	12.7 (0.500)	304 (11.97)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-1100-S	2	12.7 (0.500)	304 (11.97)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-1200-LHD	2	12.7 (0.500)	355 (13.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-1200-S	2	12.7 (0.500)	355 (13.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-1250-S	2	12.7 (0.500)	380 (14.96)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-130-S	2	12.7 (0.500)	25 (0.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-150-S	2	12.7 (0.500)	33 (1.30)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-200-LHD	2	12.7 (0.500)	51 (2.01)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-200-S	2	12.7 (0.500)	51 (2.01)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-260-LHD	2	12.7 (0.500)	69 (2.72)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-260-S	2	12.7 (0.500)	69 (2.72)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-280-S	2	12.7 (0.500)	73 (2.87)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-300-LHD	2	12.7 (0.500)	80 (3.15)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-300-S	2	12.7 (0.500)	80 (3.15)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-360-LHD	2	12.7 (0.500)	102 (4.02)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-360-S	2	12.7 (0.500)	102 (4.02)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-520-LHD	2	12.7 (0.500)	152 (5.98)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-520-S	2	12.7 (0.500)	152 (5.98)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-680-LHD	2	12.7 (0.500)	203 (7.99)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1

ST2-680-S	2	12.7 (0.500)	203 (7.99)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1
ST2-840-LHD	2	12.7 (0.500)	254 (10.00)	1112 (250)	-60 (-76)	300 (572)	Yes	AH-1
ST2-840-S	2	12.7 (0.500)	254 (10.00)	445 (100)	-60 (-76)	300 (572)	Yes	AH-1

Last Updated on 2016-07-18

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".