VFI CRO® Brand

Self-engaging Hook & Loop Tapes



HOOK & LOOP ON OPPOSITE SIDES . HOOK & LOOP ON THE SAME SIDE



Hook & Loop on Opposite Sides

A WIDE OFFERING OF BACK TO BACK TAPES WHERE HOOK AND LOOP ARE WOVEN, GLUED OR EXTRUDED TOGETHER AND GIVE DIFFERENT PERFORMANCE CHARACTERISTICS FROM HIGH CYCLE LIFE TO DISPOSABLE APPLICATIONS. BOTH HOOK & LOOP COMPONENTS OF THE CLOSURE ARE INTEGRATED IN A SINGLE PRODUCT



	FULL WIDTH HOOK COVERAGE			SINGLE HOOK LANE				
	<u> </u>	<u>0000</u>	()()()()					
CHARACTERISTICS	Double Face 200	Back to Back (Hook & Loop)	ONE-WRAP® 29	BUNDLE TIE	FLEX-ZONETM Hook 703	FLEX-ZONE™ Hook 796	FLEX-ZONE TM Hook 797	FLEX-ZONE™ Hook 898
			Hook : Polypropylene	Hook : Polypropylene	Hook : Polypropylene	Hook : Polypropylene	Hook : Polypropylene	Hook : Polypropylene
BASE MATERIAL	Polyamide	Polyamide	Backing: Velour 3800 (polyamide)	Backing: Nonwoven 3310 (polyester)	Backing: Velour 3610 (polyamide)	Backing: Velour 3905 (polyamide)	Backing: Nonwoven (polyester)	Backing : Velour 3905 (polyamide)
	Woven	Glued	Extruded Extruded					
CONSTRUCTION	Hook & Loop woven together on opposite sides	Woven Hook tape glued onto woven Loop tape	Plastic Hooks extruded onto back side of Loop material at full width		Single lane of Hooks extruded onto back side of Loop material			
CYCLE LIFE	Medium	High	Medium	Low	Medium/ Low	Medium/ Low	Medium/ Low	Medium/ Low
PEEL STRENGTH (AVERAGE)	2.6 N/cm	2 N/cm	2.1 N/cm	-	1.6 N/cm	0.9 N/cm	1.3 N/cm	1.1 N/cm
SHEAR STRENGTH (AVERAGE)	18 N/cm²	10.3 N/cm²	27 N/cm²	Min. 7 N/cm²	27 N/cm²	18 N/cm²	22 N/cm ²	20 N/cm²
	Black, white	20 colours	Black, white, yellow, green, blue, red	Moss green	Hook: Black	Hook : Black	Hook: Natural	Hook: Natural
STANDARD COLOURS					Backing: White	Backing: White, grey	Backing: White	Backing: White
STANDARD WIDTHS	25, 40	16, 20, 23, 25, 30, 38, 46, 50, 100, 125	10, 13, 16, 20, 25, 30, 38, 50, 107	10, 20	Overall: 200	Overall : 200, 300	Overall: 235	Overall: 200
(mm)					Hook lane: 30	Hook lane: 15	Hook lane: 10	Hook lane: 12
STANDARD PUT-UPS	25 m rolls	25m rolls	25m rolls	25m rolls	50m rolls	51m rolls 91m rolls	60m rolls	75m rolls
EASY PEEL FEATURE	-	-	-	-	Yes	Yes	Yes	Yes
SOME APPLICATIONS	Medical: orthopaedics Transportation: accessories Specialties: bundling	Medical: orthopaedics Specialties: bundling	Materials handling Transportation: cable protection and handling Specialties: bundling, ideal for fibre optics	Specialties: agriculture and plant tie	Materials handling Transportation: cable protection and handling Specialties: bundling			
DISTINCTIVE CHARACTERISTICS	Temperature and chemical resistance Adhesive free, no delamination High softness and flexibility	Flexibility High cycle life	Hook-loop lamination without the use of adhesives Strong self-engaging	Hook-nonwoven lamination without the use of adhesives Disposable self-engaging	Disposable self-engaging			

Hook & Loop on the Same Side

WOVEN TAPES WHERE HOOK AND LOOP ARE WOVEN SIDE BY SIDE OR MIXED ON THE SAME FACE OF THE TAPE. ITS WOVEN TECHNOLOGY AND HIGH PROFILE SHAPE PROVIDE HIGH PERFORMANCE ON ENGAGEMENT VALUES. BOTH HOOK & LOOP COMPONENTS OF THE CLOSURE ARE INTEGRATED IN ONE PRODUCT




	HOOK & LOOP MIXED	HOOK & LOOP SIDE BY SIDE			
	<u>.cancacan</u>	OCC (000000000)	<u>.C.C.C. ((((()))</u>		
CHARACTERISTICS	OMNI-TAPE®	Side by Side Standard	Side by Side PS14		
BASE MATERIAL	Polyamide	Polyamide	Polyamide		
CONSTRUCTION	Woven	Woven			
CONSTRUCTION	Hook & Loop woven together and mixed	Hook & Loop woven side by side with a separation in between			
CYCLE LIFE	High	High	High		
PEEL STRENGTH (AVERAGE)	1.22 N/cm	1.2 N/cm	1.2 N/cm		
SHEAR STRENGTH (AVERAGE)	8.4 N/cm²	13 N/cm²	13 N/cm²		
STANDARD COLOURS	Black, white	Black, white	Black, white		
STANDARD WIDTHS (mm)	20, 25, 50	50, 80	50		
STANDARD PUT-UPS	25m rolls	25m rolls	25m rolls		
SOME APPLICATIONS	Medical: orthopaedics Industrial: high quality apparel, leather jackets	Medical: plasters Specialties: furnishing covers	Specialties: cable guide, upholstery		
DISTINCTIVE CHARACTERISTICS	Avoid scratching (loops protecting the hooks) Closing system with a channel Protection High cycle life				

			TYPES OF CLOSURES			
			HOOK & LOOP ON OPPOSITE SIDES	HOOK & LOOP ON THE SAME SIDE		
	WOVEN	0000	Double face 200	OMNI-TAPE® Side by Side		
TECHNOLOGY	GLUED	200	Back (to Back (Hook & Loop)			
	EXTRUDED		ONE-WRAP® 29 / BUNDLE TIE FLEX-ZONE™			

VFI CRO® Branc

ONE-WRAP® Straps

PATENTED ONE-WRAP® & FLEX-ZONE™ TECHNOLOGIES PROVIDE THE ABILITY TO EXTRUDE HOOKS OR FLAT-ZONES CONTINUOUSLY ON A VARIETY OF LAMINATES AND SUBSTRATES



SIZE	STRAPS/ SPOOL	STRAP SHAPE	
13x200 mm	750	13x200	
20x150 mm	1.000	20x150	
20x200 mm	750	20x200	
20x230 mm	650	20x230	
20x330 mm	450	20x330 13 mm	
25x300 mm	500	25x300	
10x150 mm	1.200	10x150	
12x210 mm	700	12x210	

VELCRO® Brand

FLEX-ZONE™ Pieces



Maximum length 1500mm

Standard tape widths 200, 235, 260 and 300mm


Easy peel option

Pre-cut piece


VELCRO® Brand


Pre-cut pieces in rolls





Customised length from 200 to 550 mm





Minimum strap length Maximum strap length

Some strap length options

METHODS OF ATTACHMENT



Pressure sensitive adhesives

(See VELCRO® Brand Adhesives Range)







Heat or solvent activated adhesives

(See VELCRO® Brand Adhesives Range)





FABRICATION



Slitting



Scored cut



Custom manufactured straps



Pre-cut



Mated



Complete product assembly




Die cut



Perforated

PRINTING



Flexography



Hot stamping



Pad printing



Heat transfer labels

PACKAGING



Rolls



Spools









Sealed bag



Blister



Folding boxes



Bundling



Bulk



Customised packaging

APPLICATIONS



















VELCRO INDUSTRIES ARE WORLDWIDE LEADERS IN FASTENING SYSTEMS OFFERING A WIDE RANGE OF SOLUTIONS, FROM STANDARD HOOK AND LOOP TO COMPLETE FINISHED PRODUCTS.

50 YEARS OF EXPERIENCE: WE ARE PROUD OF OUR HERITAGE IN INNOVATION HAVING OVER 300 ACTIVE PATENTS TO OFFER BETTER SOLUTIONS TO SATISFY OUR CUSTOMERS' NEEDS.



























USA

Velcro USA Inc. Tel: (+800) 225 0180 marketing@velcro.com www.velcro.com

Canada

Velcro Canada Inc. Tel: (+800) 683 5276 canada@velcro.com www.velcro.ca

Mexico

Velcro de Mexico, S.A. de C.V. Tel: (+52) 55 5005 3300 salesmc@velcro.com www.velcrodemexico.com

Spain

Velcro Europe S.A. Tel: (+34) 93 758 32 98 infovelcro@velcro.es www.velcro.es

Germany

Velcro GmbH Tel: (+49) 7141 991 19-0 info@velcro.de www.velcro.de

France

Velcro Industries France S.A.S. Tel: (+33) 0 1 34 38 78 88 info@velcro.fr www.velcro.fr

Italy

Velcro Italia, S.R.L. Tel: (+39) 039 62 70 01 commerciale@velcro.com www.velcro.it

UK

Velcro Limited Tel: (+44) 1606 73 88 06 uksales@velcro.com www.velcro.co.uk

Australia

Velcro Australia Pty. Ltd. Tel: (+61) 3 9703 2466 sales@velcro.com.au www.velcro.com.au

China

Velcro China Fastening Systems Company Limited Tel: (+86) 21 6045 2090 (Shanghai Sales Office) www.velcro.com.cn

Hong Kong

Velcro Hong Kong Ltd. Tel: (+852) 2570 3698

VELCRO INDUSTRIES AROUND THE WORLD

